

IN THE CLAIMS:

Claims 8 through 10, 21 through 52 and 56 were previously cancelled. Claims 1, 53 and 55 have been amended herein. All of the pending claims are presented below. This listing of claims will replace all prior versions and listings of claims in the application. Please enter these claims as amended.

1. (Currently amended) An electrode for use in obtaining a ~~non-invasive~~ noninvasive impedance measurement of tissue constituents from a subject, comprising:
an electrically insulative substrate; and
at least two discrete, linear, elongate conductive elements carried by the electrically insulative substrate with at least regions of adjacent conductive elements that are not carried by the electrically insulative substrate being spaced apart from one another a distance that facilitates the ~~non-invasive~~ noninvasive impedance measurement of tissue constituents, each elongate conductive element including a contact region.
2. (Previously presented) The electrode of claim 1, wherein a pair of elongate conductive elements of the at least two elongate conductive elements extends in substantially a common direction.
3. (Previously presented) The electrode of claim 2, wherein the elongate conductive elements of the pair are oriented substantially parallel to one another.
4. (Previously presented) The electrode of claim 3, wherein the elongate conductive elements of the pair have substantially the same widths.
5. (Previously presented) The electrode of claim 4, wherein the elongate conductive elements of the pair are spaced apart from one another by a distance which is substantially the same as the width of each elongate element.

6. (Previously presented) The electrode of claim 5, wherein the electrically insulative substrate has a width equal to about four times the width of each elongate element.

7. (Previously presented) The electrode of claim 6, wherein a gap between the elongate elements of the pair is positioned substantially centrally relative to the width of the electrically insulative substrate.

8.-10. (Canceled)

11. (Previously presented) The electrode of claim 1, wherein the contact region includes at least one aperture formed therethrough.

12. (Original) The electrode of claim 11, wherein the at least one aperture is elongate.

13. (Previously presented) The electrode of claim 1, wherein each elongate conductive element includes an electrical contact configured to be folded in half to include oppositely facing electrically conductive surfaces.

14. (Previously presented) A strip of electrodes, comprising two offset rows of at least partially overlapping electrode pairs, each electrode pair including:
a common contact region; and
a pair of spaced apart elongate elements extending from the common contact region and oriented substantially parallel to one another,
common contact regions of adjacent electrode pairs in the same row being positioned adjacent to one another and forming an edge of the strip,
elongate elements of electrode pairs in the same row being aligned with one another and oriented substantially parallel to each other,
adjacent elongate elements of each row being spaced apart by an elongate element of an electrode pair of the other row.

15. (Original) The strip of claim 14, wherein all of the elongate elements of the electrode pairs have substantially the same widths and are spaced apart from one another by a distance which is substantially equal to a width of each elongate element.

16. (Original) The strip of claim 14, comprising:
a substantially confluent dielectric layer;
a patterned conductive layer on the substantially confluent dielectric layer; and
a conductive coating layer over the patterned conductive layer only at locations of the strip that include the elongate elements.

17. (Previously presented) The strip of claim 16, wherein the patterned conductive layer forms a pair of electrical contacts at the common contact region of each electrode pair and an electrode that communicates with a corresponding electrical contact and forms a part of each elongate element.

18. (Previously presented) The strip of claim 16, wherein the substantially confluent dielectric layer includes at least one row of apertures formed through the common contact regions of each row of electrode pairs.

19. (Previously presented) The strip of claim 18, wherein the substantially confluent dielectric layer includes two rows of apertures formed through the common contact regions of each row of electrode pairs.

20. (Previously presented) The strip of claim 19, wherein the common contact region of each electrode pair is configured to be folded in half such that two apertures formed therethrough are aligned with one another and a pair of electrical contacts thereon are exposed to both major surfaces of the electrode pair.

21.-52. (Canceled)

53. (Currently amended) An electrode strip, comprising:
a pair of electrodes spaced apart from one another by a distance that facilitates a ~~non-invasive~~
noninvasive impedance measurement of tissue constituents; and
at least another electrode interleaved between electrodes of the pair and configured to be
removed from between the pair of electrodes prior to use of the electrodes and the at least
another electrode.

54. (Previously presented) The electrode strip of claim 53, wherein the pair of
electrodes are physically secured to one other by way of an electrically non-conductive element.

55. (Currently amended) The electrode pair of claim 53, wherein the pair of ~~electodes~~
electrodes extend substantially parallel to one another.

56. (Canceled)

57. (Previously presented) The electrode pair of claim 53, wherein a contact region of
each electrode is configured to be folded in half such that a pair of electrical contacts are exposed
to both major surfaces of the electrode.